

lammina

16AL SUPERLIGHT

Aluminum Tenders



S P E C S

Overall Length	: 16' / 4.88m	Number of Chambers	: 5	Shaft Length	: 20" / 50.8cm
Overall Beam	: 7' / 2.14m	Person Capacity	: 10	RDC Design Category	: C
Inside Length	: 12'8" / 3.85m	Weight	: 409lb / 186kg		
Inside Beam	: 3'6" / 1.08m	Recommended HP	: 50hp / 37.3kw		
Tube Diameter	: 20" / 0.51m	Maximum HP	: 60hp / 44.8kw		

S T A N D A R D
F E A T U R E S

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee
- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Orca(CSM) Five Layer Coated Fabric
- Raised Double Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Quadruple Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Sets of Triple Orca (CSM) Fabric Handles on Tubes
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

O P T I O N A L
F E A T U R E S

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bow Locker/ Seat

