



A B I N F L A T A B L E S

lammina

8 AL SUPERLIGHT

Aluminum Tenders



S P E C S

Overall Length	: 8'5" / 2.56m	Number of Chambers	: 3	Shaft Length	: 15" / 38.1cm
Overall Beam	: 4'9" / 1.45m	Person Capacity	: 4	RDC Design Category	: C
Inside Length	: 5' 10" / 1.79m	Weight	: 73lb / 33kg		
Inside Beam	: 2' / 0.62m	Recommended HP	: 4hp / 3.0kw		
Tube Diameter	: 16" / 0.40m	Maximum HP	: 6hp / 4.5kw		

S T A N D A R D
F E A T U R E S

- Deep "V" Marine Grade Aluminum Hull
- Heavy Duty Transom Knee
- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip
- Aluminum Bow Eye
- 3 Aluminum Davit Lifting Points
- Deck Drain with Plug
- Orca(CSM) Five Layer Coated Fabric
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Single Rub Rail
- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Single Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
- Removable Rowing Seat
- Oarlock Bases
- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

O P T I O N A L
F E A T U R E S

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel cleat
- Lateral Fold Down Stainless Steel Cleat

